## **Britannia Premier** Cartridge Operated Fire Extinguisher BT6 - BSX Foam









## BT6 **BSX Foam**



The Triclass foam spray fire extinguisher has excellent firefighting capabilities making it effective on Class A materials fuelled by wood, paper and textiles as well as Class B fires fuelled by paints, solvents, oils and petrochemical products.

The extinguisher has also passed the EN3 test for use on live electrical equipment up to 1000V at a distance of 1m. The operational temperature range is from +5°c to +60°c.

## **Features**

- Manufactured in Great Britain
- Britannia offer a 7 year quality guarantee against material defects and workmanship
- Die cast zinc colour coded headcap
- · Large neck ring enables servicing, refilling and internal inspection to be conducted with ease
- 55 gram CO<sub>2</sub> cartridge
- All weather service indicator studs
- Additional anti-corrosion treatment available
- · High quality internal polythene lining to protect against corrosion
- Frost protection is available
- Main approvals and certifications as below







| TECHNICAL SPECIFICATION |                   |                |                      |               |                                    |                              |                        |                  |             |  |
|-------------------------|-------------------|----------------|----------------------|---------------|------------------------------------|------------------------------|------------------------|------------------|-------------|--|
| Model                   | Capacity (Litres) | Fire<br>Rating | Full Weight<br>(Kgs) | Temp<br>Range | Operating Pressure<br>(Bar) @ 20°C | Discharge<br>Duration (Secs) | Discharge<br>Range (M) | Diameter<br>(mm) | Height (mm) |  |
| BT6                     | 6                 | 21A/144B       | 11.4                 | +5° to + 60°C | 12                                 | 40                           | 4+                     | 165              | 525         |  |

| SPECIFICATIONS                        |   |  |  |  |  |  |
|---------------------------------------|---|--|--|--|--|--|
| Gas Cartridge                         | 55gram CO <sub>2</sub>                              |  |  |  |  |  |
| Operating Pressure @ 20°C             | 12bar   |  |  |  |  |  |
| Test Pressure (PT)                    | 26bar   |  |  |  |  |  |
| Maximum Allowable Pressure (PS)       | 18bar   |  |  |  |  |  |
| Minimum Burst Pressure                | 55bar   |  |  |  |  |  |
| Cylinder Material                     | 1.6mm Thick Mild Steel to EN 10111 - DD12           |  |  |  |  |  |
| Operating Head Material               | Zinc Alloy to EN 1774 - ZnA14 (ZL3)                 |  |  |  |  |  |
| Hose and Spray Nozzle                 | Hose - EPDM Synthetic Rubber                        |  |  |  |  |  |
| Finish - Red RAL3000 UV Protection    | Polyester Powder Paint - Thickness (85 microns avg) |  |  |  |  |  |
| Anti-Corrosion Treatment if Requested | Zinc Coating  |  |  |  |  |  |

| COMPONENT PARTS |   |             |  |  |  |  |  |  |
|-----------------|---|-------------|--|--|--|--|--|--|
| Item            | Description   | Part No.    |  |  |  |  |  |  |
| А               | Headcap Assembly  | BRH1030     |  |  |  |  |  |  |
| В               | Welded Body Assembly  | BODYML      |  |  |  |  |  |  |
| С               | Syphon Tube Assembly  | BRH-ST06F   |  |  |  |  |  |  |
| D               | Gas Tube Assembly   | BR0675      |  |  |  |  |  |  |
| Е               | Skirt Ring  | BRH0465     |  |  |  |  |  |  |
| F               | Cartridge   | C55         |  |  |  |  |  |  |
| G               | Hose Assembly and Nozzle  | BR0493      |  |  |  |  |  |  |
| Н               | Service Indicator Stud (Colour Coded)  1. Service Year, 2. Discharge Year | BRH0185     |  |  |  |  |  |  |
| I               | Oetiker Clip  | BR0540      |  |  |  |  |  |  |
| J               | Safety Pin  | BRH0180     |  |  |  |  |  |  |
| K               | Nut Ring  | BRH0105     |  |  |  |  |  |  |
| L               | Sleeve  | BRH0150     |  |  |  |  |  |  |
| М               | Spring  | BRH0200     |  |  |  |  |  |  |
| Ν               | O Ring  | BRH0230     |  |  |  |  |  |  |
| 0               | Valve Control Assembly  | BRH0400     |  |  |  |  |  |  |
| Р               | Cartridge/Valve Holder  | BRH0120     |  |  |  |  |  |  |
| Q               |   |             |  |  |  |  |  |  |
| R               |   |             |  |  |  |  |  |  |
| S               |   |             |  |  |  |  |  |  |
| Т               |   |             |  |  |  |  |  |  |
| U               |   |             |  |  |  |  |  |  |
| V               | Transport Bracket & Strap   | BRH0311     |  |  |  |  |  |  |
| -               | Pull Tight Seal   | BRH0175     |  |  |  |  |  |  |
| -               | Wall Bracket  | BRH0195     |  |  |  |  |  |  |
| -               | 6ltr BSX Foam refill  | AFFT06      |  |  |  |  |  |  |
| -               | Cartridge Spanner   | SPANNER22MM |  |  |  |  |  |  |
| -               | Headcap Spanner   | HCS         |  |  |  |  |  |  |
| -               | Valve Holder Ring Spanner   | SPANNER27MM |  |  |  |  |  |  |



