


Blazex CO₂ Fire Extinguisher BXC2 - Carbon Dioxide



CO₂



BXC2 Carbon Dioxide



Carbon Dioxide is tested on Class B (flammable liquid) fires and is used as a clean extinguishing agent on small fires.

PLEASE NOTE: For every 1kg of CO₂ in your premises you must ensure you have 5.5 metres of space.

Features

- Manufactured in Great Britain 
- Britannia offer a 10 year quality guarantee against material defects and workmanship
- Brass nickel plated valve with colour coded levers and screen
- Aluminum body
- Swivel Horn (Frost Free)
- Main approvals and certifications as below

EN3



TECHNICAL SPECIFICATION

Model	Capacity (Kg)	Fire Rating	Full Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Diameter (mm)	Height (mm)
BXC2	2	34B	5.2	-20° to + 60°C	50	10	3	117	500

SPECIFICATIONS

Operating Pressure @ 20°C	50bar
Test Pressure (PT)	212bar
Maximum Allowable Pressure (PS)	169.3bar
Cylinder material	Aluminum Alloy
Operating Valve Material	Brass Material - EU grade CuZn40Pb2 - EU code CW617N
Horn Material	Polyethylene
Finish - Red RAL3000 UV Protection	Polyester Powder Paint - Thickness (85 microns avg)

COMPONENT PARTS

Item	Description	Part No.
A	Swivel Horn and Elbow (Frost Free)	BC010
B	Brass Parallel Valve	VLV0015
C	2kg Alloy CO ₂ Cylinder	CYL0035
D	Syphon Tube	TUBE0183
E		
F	Safety Pin and Ring	BC055
-	Pull Tight Seal	BRH0175
-	Wall Bracket	BRH0540

