Blazex Stored Pressure Fire Extinguisher **BXF9 - BSX Foam**









BXF9 **BSX Foam**



The Blazex Triclass foam spray fire extinguisher has excellent firefighting capabilities making it effective on Class A materials fuelled by wood, paper and textiles as well as Class B fires fuelled by paints, solvents, oils and petrochemical products.

The extinguisher has also passed the EN3 test for use on live electrical equipment up to 1000v at a distance of 1m. The operational temperature range is from +5°C to +60°C.

Marine Model Available.

Features

- Manufactured in Great Britain
- Britannia offer a 5 year quality guarantee against material defects and workmanship
- Colour coded screen
- Pressure indicator gauge (magnetic)
- Brass nickel plated valve
- Additional anti-corrosion treatment available
- · High quality internal polythene lining to protect against corrosion
- Frost protection is available
- Main approvals and certifications as below









TECHNICAL SPECIFICATION										
Model	Capacity (Litres)	Fire Rating	Full Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Diameter (mm)	Height (mm)	
BXF9	9	21A/183B	14.2	+5° to + 60°C	12	60	4	190	585	

SPECIFICATIONS	
Operating Pressure @ 20°C	12bar
Test Pressure (PT)	26bar
Maximum Allowable Pressure (PS)	18bar
Minimum Burst Pressure	55bar
Cylinder Material	1.6mm Thick Mild Steel to EN 10111 - DD12
Operating Valve Material	Brass Material - EU grade CuZn40Pb2 - EU code CW617N - plus Nickel Plating
Hose and Spray Nozzle	Hose - EPDM Synthetic Rubber
Finish - Red RAL3000 UV Protection	Polyester Powder Paint - Thickness (85 microns avg)
Anti-Corrosion Treatment if Requested	Zinc Coating

COMPONENT PARTS							
Item	Description	Part No.					
А	Headcap Assembly	BRHXF9					
В	Syphon Tube Assembly	XDT0002					
С	Skirt Ring	BRH0460					
D	Hose Assembly and Nozzle	IC0495					
Е	Oetiker Clip	BR0540 & 541					
F	Safety Pin	BRH0181					
G	Magnetic Pressure Indicator Gauge	P50GM9					
Н	Transport Bracket & Strap	BRH0310					
-	Pull Tight Seal	BRH0175					
-	Wall Bracket	BRH0195					
-	9kg BSX Foam refill	AFFT09					





