## **Norfolk Premier** Mobile Fire Extinguisher NRAF135 - BSX Foam







## NRAF135 **BSX Foam**



The BSX foam fire extinguisher has excellent firefighting capabilities making it effective on Class A materials fuelled by wood, paper and textiles as well as Class B fires fuelled by paints, solvents, oils and petrochemical products.

The operational temperature range is from  $+5^{\circ}$ C to  $+60^{\circ}$ C.

Rough terrain double bogey wheels are available.

## **Features**

Manufactured in Great Britain



- Britannia offer a 10 year quality guarantee against material defects and workmanship
- Colour coded labels
- External CO<sub>2</sub> side cylinder
- Polyester Red (RAL 3000) coating externally and Polymer coating internally gives maximum protection against corrosion
- Main approvals and certifications as below









TECHNICAL SPECIFICATION											
Model	Capacity (Litres)	Fire Rating	Full Weight (Kgs)	Empty Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Width (mm)	Depth (mm)	Height (mm)
NRAF135	135	IVB	224	88	+5° to + 60°C	14.5	200	14	710	770	1230

SPECIFICATIONS			
Side Cylinder	1.0kg CO <sub>2</sub>		
Operating Pressure @ 20°C	14.5bar		
Test Pressure (PT)	32bar		
Maximum Allowable Pressure (PS)	22bar		
Minimum Burst Pressure	59.4bar		
Safe Operating Distance	5m		
Cylinder Material	5mm Thick Mild steel to EN 10111 - DD12		
Nut Ring	Zinc Alloy to EN 1774 - ZnA14 (ZL3)		
Headblock	Brass C3771		
CO <sub>2</sub> Hose	Synthetic rubber reinforced with high tensile wire braid		
Paint Finish/Colour	Polyester Red (RAL 3000)		
Discharge Hose - 6m (alternative lengths avail on request)	6m Reinforced Rubber		

COMPONENT PARTS							
Item	Description	Part No.					
Α	Body Assembly	NR0165KB					
В	1.0KG Side Cylinder with Valve	NCS1000					
С	6m Discharge Hose Assembly	HS0010					
D	Foam Control Lance/Swivel Connector	HS0410					
Е	Nut Ring	BRH0105					
F	Brass Headblock Assembly	NRH0560					
G	CO <sub>2</sub> Hose Assembly	HS0130					
Н	Solid Rubber Wheels 400mm diameter	WHLS030					
1	Washer	WC0140					
J	Split pin	WC0150					
K	Swivel Connector	NRH0360F					
-	Syphon Tube (Internal)	NRH0575					
-	Gas Tube (Internal)	NRH580					
-	Pull Tight Seal	BRH0175					
-	2.03ltr BSX Foam Charge Refill	FOAM250					
-	Headcap Spanner	HCS					

