## Norfolk Premier Mobile Fire Extinguisher NWS50 - BC Dry Powder











## NWS50 BC Dry Powder



BC powder is based on Sodium bicarbonate. The extinguishing powder interferes with the chemical reactions that take place in the combustion zone, thus the flame ceases to exist and the fire is extinguished.

The powder is nonconductive and may be used in the presence of an electric current.

BC powder will extinguish Class B (flammable liquid) fires and Class C (flammable gas) fires.

Rough terrain double bogey wheels are available.

## **Features**

- Manufactured in Great Britain
- Britannia offer a 10 year quality guarantee against material defects and workmanship
- Colour coded labels
- External CO<sub>2</sub> side cylinder
- Additional Anti-Corrosion Treatment Available
- · Also available as a lower cost Super BC powder model
- Main approvals and certifications as below



TECHNICAL SPECIFICATION												
Model	Capacity (Kg)	Full Weight (Kgs)	Empty Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Width (mm)	Depth (mm)	Height (mm)		
NWS50	50	94	42.65	-30° to + 60°C	11.5	35	14	510	610	980		

SPECIFICATIONS			
Side Cylinder	1.35kg CO <sub>2</sub>		
Operating Pressure @ 20°C	11.5bar		
Test Pressure (PT)	32bar		
Maximum Allowable Pressure (PS)	22bar		
Minimum Burst Pressure	59.4bar		
Safe Operating Distance	5m		
Cylinder Material	3mm Thick Mild steel to EN 10111 - DD12		
Nut Ring	Zinc Alloy to EN 1774 - ZnA14 (ZL3)		
Headblock	Brass C3771		
CO <sub>2</sub> Hose	Synthetic rubber reinforced with high tensile wire braid		
Finish - Red RAL3000 UV Protection	Polyester Powder Paint - Thickness (85 microns avg)		
Anti-Corrosion Treatment if Requested	Zinc Coating		
Discharge Hose - 5m (alternative lengths avail on request)	Reinforced Rubber		

COMPONENT PARTS										
Item	Description	Part No.								
Α	Body Assembly	NR0155KB								
В	1.35KG Side Cylinder with Valve	NCS1350								
С	5m Discharge Hose Assembly	HS0030								
D	Powder Control Lance/Swivel Connector	HS0400								
Е	Nut Ring	BRH0105								
F	Brass Headblock Assembly	NRH0580								
G	CO <sub>2</sub> Hose Assembly	HS0130								
Н	Solid Rubber Wheels 300mm diameter	WHLS015								
1	Washer	WC0140								
J	Split pin	WC0150								
K	Swivel Connector	NRH0360								
L	Filling Funnel	FILLINGFUNNEL								
-	Pull Tight Seal	BRH0175								
-	50kg BC Dry Powder Refill	PM50								
-	Headcap Spanner	HCS								



